

BEST AVAILABLE COPY



JAPANESE PATENT OFFICE



PATENT ABSTRACTS OF JAPAN

(11) Publication number:

09192230 A

(43) Date of publication of application: 29.07:1997

√ (51) Int. Cl

A61M 25/00

A61M 25/01

(21) Application number:

08029891

(22) Date of filing:

23.01.1996

(71) Applicant: FUKUDA TOSHIO

ARAI FUMITO

(72) Inventor.

FUKUDA TOSHIO

: ARAI FUMITO

(54) CATHETER IN BLOOD VESSEL


(57) Abstract:

PROBLEM TO BE SOLVED: To improve safety of operation of a catheter insertion work by providing a detection part having one or a plurality of projections at its end and providing a pressure sensor, which measures the pressure of a contact part by contacting a projection with environmental substance on the catheter tip.

SOLUTION: When a projection 2 in the adjacent to the end of the detection part is brought in contact with environmental substance, a detection part 3 is pushed so that a pressure sensor 1 reads changes in pressure applied on a pressure transmission medium 6. The pressure sensor 1 is mounted on the tip of the catheter

and at the same time an actuator 11 oscillating the a jacent of the catheter tip is installed. The root of the actuator 11 is fixed in the tube by swelling one of lot of balloons 12 which are provided in the adjace to the root of the actuator 11 so that the actuator is oscillated. The advancing direction of the cathetip is selected by scraping off the environmental action by recessed/projecting face of the catheter 1 and actively controlling the actuator 11.

COPYRIGHT: (C)1997,JPO







DELPHION

No active trail







- अनुविधार प्रकृति होस्य हिस्स्य हिस्स्य हिस्स्य

My Account

RESEARCH

Search: Quick/Number Boolean Advanced Derwent

The Delphion Integrated View

Get Now: PDF | More choices...

Tools: Add to Work File: Create new Work File

View: INPADOC | Jump to: Top

Go to: Derwent

Email this

Title:

JP09192230A2: CATHETER IN BLOOD VESSEL

*Derwent Title:

Catheter for blood vessel - has force sensor to measure force of contact part when protrusion at end vicinity of detection part contacts surroundings

[Derwent Record]

© Country:

JP Japan

Α

VInventor:

FUKUDA TOSHIO;

ARAI FUMITO;

PAssignee:

FUKUDA TOSHIO

ARAI FUMITO

News, Profiles, Stocks and More about this company

Published / Filed:

1997-07-29 / 1996-01-23

PApplication

JP1996000029891

Number:

FIPC Code: A61M 25/00; A61M 25/01;

Priority Number:

1996-01-23 JP1996000029891

PAbstract:

PROBLEM TO BE SOLVED: To improve safety of operation of a catheter insertion work by providing a detection part having one or a plurality of projections at its end and providing a pressure sensor, which measures the pressure of a contact part by contacting a projection with environmental substance on the catheter tip.

SOLUTION: When a projection 2 in the adjacent to the end of the detection part is brought in contact with environmental substance, a detection part 3 is pushed so that a pressure sensor 1 reads changes in pressure applied on a pressure transmission medium 6. The pressure sensor 1 is mounted on the tip of the catheter and at the same time an actuator 11 oscillating the adjacent of the catheter * tip is installed. The root of the actuator 11 is fixed in the tube by swelling one or a lot of balloons 12 which are provided in the adjacent to the root of the actuator 11 so that the actuator 11 is oscillated. The advancing direction of the catheter tip is selected by scraping off the environmental substance by recessed/projecting face of the catheter tip, and actively controlling the actuator 11.

COPYRIGHT: (C)1997,JPO


PFamily:

None


POther Abstract

None









THOMSON

this for the Gallery...

Copyright © 1997-2005 The Thomson

Subscriptions | Web Seminars | Privacy | Terms & Conditions | Site Map | Contact Us |

BEST AVAILABLE COPY